

► Features

- High-fidelity, full range reproduction of music and speech
- Coverage pattern 90° x 75°
- Vertical or Horizontal coverage
- 12 Built-in rigging points
- Stand fitting built in bottom
- Scratch-free EPDM coating

► Applications

- Concerts
- Clubs
- Pubs
- Indoor festivals
- Athletic fields
- Events



AUDAC's PX115 cabinet is a compact, full range loudspeaker designed to be used especially in indoor installations.

It delivers a clear and natural sound. The loudspeaker has a 15" cone driver and a 1.3" HF driver with a coverage pattern of 90° x 75° and is designed to work vertically as well as horizontally.

Average power handling is 300W. On-axis frequency range is 60Hz to 19kHz. On-axis sensitivity (1W/1m) is 100 dB SPL and even reaches a maximum SPL of 125 dB.

For extra safety, there's a protection circuit placed inside to protect the 1.3" tweeter when overload occurs.

The PX series have a MDF wooden enclosure with scratch free, durable textured EPDM black painting and ergo grips.

The built-in bottom 35 mm speaker stand adapter can be replaced by a M10 screw flange. With M10 screw flange attachment points on top and bottom, the PX115 can be mounted in any direction with an optional suspension bracket. With the 12 rigging points on every side of the speaker, it's also possible to let him fly.

At the back of the PX115, there are two Speakon NL4MP Neutrik connectors. One of these two Speakon connectors can be used for linking a second PX115 to the first one.

Optional accessoires:

- CPB115P Cover bag
- MBK115 Wallbracket

► Specifications

SYSTEM SPECIFICATIONS		
Max power	600 W	
RMS power	300 W	
Impedance speaker	8 Ohm	
Sound pressure 1W/1m	100 dB	
Sound pressure Max W/1m	125 dB	
Frequency response -3dB	60 Hz - 19 kHz	
Frequency range -10dB	45 Hz - 20 kHz	
Cross-over frequency	2 kHz	
Crossover network	Passive built-in	
Horizontal coverage	90°	
Vertical coverage	75°	
PRODUCT FEATURES		
Dimensions (Width x Height x Depth)	435 x 765 x 495 mm	
Weight net	35 Kg	
Drivers	HF 1,3" / MF 15"	
Connectors	2 x Speakon NL4MP Neutrik	
Construction	Medium density wood with EPDM black coating	
Front finish	Perforated steel grill	
Rigging flying points	12 x M10	
Carry handles	Two at the sides	
Rigging stand fitting	Built-in bottom 35 mm + top M10	
Colour	Black	PX115/B
	White	PX115/W
SHIPPING & ORDERING		
Packaging	Carton box	
Shipping weight & volume	37 Kg - 0.23 Cbm	
Accessories	CPB115P Protective cover bag	
	MBK115 wall bracket + Safety	
*AUDAC reserves the right to change specifications without notice: this is part of our policy to continually improve our products		